(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 28 April 2005 (28.04.2005)

PCT

(10) International Publication Number WO 2005/038092 A1

(51) International Patent Classification7:

C25C 5/00

(21) International Application Number:

PCT/AU2004/001410

(22) International Filing Date: 14 October 2004 (14.10.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2003905595

14 October 2003 (14.10.2003) AU

(71) Applicant (for all designated States except US): BHP BIL-LITON INNOVATION PTY LTD [AU/AU]; BHP Billiton Centre, 180 Lonsdale Street, Melbourne, Victoria 3000 (AU).


(72) Inventors; and

(75) Inventors/Applicants (for US only): RIGBY, Gregory, David [AU/AU]; 107 Tirriki Street, Charles Town, New South Wales 2290 (AU). RATCHEV, Ivan [AU/AU]; 2 Young Street, Georgetown, New South Wales 2298 (AU). SHOOK, Andrew, Arthur [AU/AU]; 4 Orlando Close, Eleebana, New South Wales 2282 (AU).

(74) Agent: GRIFFITH HACK; 509 St Kilda Road, Melbourne, Victoria 3004 (AU).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:



cathode. The process is characterised by supplying an amount of electrolyte into the bath that is greater than the amount of electrolyte that is required to replace electrolyte removed from the bath with reduced material and removing molten electrolyte from the bath to maintain the bath height at a required height or within a range of required heights.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.